

NEWAY klepzittingfrezen, gesorteerd op body Ø en benodigde mesjes, T-sleutel en geleiderpennen

U heeft minimaal nodig: 1 x frees - 1 x geleiderpen - 1 x T-sleutel

Frees nr. serie 100	Body Ø mm	Hoeken	Freesbereik mm		Mesjes nr.	Aantal	T-sleutel	Geleiderpen/Pilot
134	19.3	15°	16.5-18		250	3	TW513	100 + 120
130	20.7	15°	18-19.5		250	3	TW513	100 + 120
132	21.1	32°	18.5-20		250	3	TW513	100 + 120
135	21.1	45°	18.5-21		250	3	TW513	100 + 120
138	22.1	20°	19.5-21		250	3	TW513	100 + 120
133	22.2	60°	18-22		250	3	TW513	100 + 120
143	23.5	45°	21-23.5		250	3	TW513	100 + 120
120	25.4	15°	22.5-25.5		253	3	TW513	100 + 120
121	25.4	15°	22.5-26.5		253	3	TW513	100 + 120
127	25.4	20°	22-26		253	3	TW513	100 + 120
126	25.4	30°	24.5-28.5		250	3	TW513	100 + 120
115	25.4	31°	24.5-28.5		250	3	TW513	100 + 120
122	25.4	45°	22.5-29		253	3	TW513	100 + 120
110	25.4	46°	22.5-29		253	3	TW513	100 + 120
111	25.4	60°	22-32.5		252	3	TW513	100 + 120
103	28.6	31°/46°	25-30.5	25-32	253	3 + 3	TW513	100 + 120
114	31.8	60°	28.5-36		252	3	TW513	100 + 120
124	33.3	15°/60°	32.5-39.5	32.5-44.5	251 + 254	3 + 3	TW513	100 + 120
128	33.3	30°/45°	30-36	30-38.5	250 + 250	3 + 3	TW513	100 + 120
102	33.3	31°/46°	31-41	30-40.5	251 + 251	3 + 3	TW513	100 + 120

Frees nr. serie 200 600 + 700	Body Ø mm	Hoeken	Freesbereik mm		Mesjes nr.	Aantal	T-sleutel	Geleiderpen/Pilot
243	28.6	15°	25.5-32.5		250	3	TW505	140 + 150 + 200
274	28.6	30°/45°	29-33.5	33.5-28.5	250	3 + 3	TW505	140 + 150 + 200
278	28.6	30°	25.5-32		250	3	TW505	140 + 150 + 200
268	28.6	45°	25.5-33.5		250	3	TW505	140 + 150 + 200
269	28.6	60°	25-35		252	3	TW505	140 + 150 + 200
701	31.8	0°	28.8-35.4		250	3	TW505	140 + 150 + 200
204	31.8	15°/46°	29-35	29-37	250	3 + 3	TW505	140 + 150 + 200
212	31.8	15°/75°	28.5-35	28.5-38.5	250/254	3 + 3	TW505	140 + 150 + 200
244	31.8	15°	28.5-35		250	3	TW505	140 + 150 + 200
273	31.8	15°/60°	29-35	29-38.5	250/252	3 + 3	TW505	140 + 150 + 200
603	31.8	15°/31°	28.5-35	28.5-35	250	3 + 5	TW505	140 + 150 + 200
606	31.8	25°	28.5-36		250	5	TW505	140 + 150 + 200
230	31.8	30°/45°	29-35	28.5-37	250	3 + 3	TW505	140 + 150 + 200
203	31.8	31°/46°	28.5-34.5	28.5-37	250	3 + 3	TW505	140 + 150 + 200
285	31.8	46°	28.5-37.5		250	3	TW505	140 + 150 + 200
270	31.8	60°	28.5-38		252	3	TW505	140 + 150 + 200
222	31.8	70°	28.5-37.5		252	3	TW505	140 + 150 + 200
209	35.0	15°/46°	31.5-37	31.5-40.5	250	3 + 3	TW505	140 + 150 + 200
612	35.0	15°/46°	32-37.5	32-40.5	250	3 + 5	TW505	140 + 150 + 200
615	35.0	15°/45°	32-37.5	32-40.5	250	3 + 5	TW505	140 + 150 + 200
221	35.0	20°/45°	31.5-37.5	32.5-44.5	250/251	3 + 3	TW505	140 + 150 + 200
232	35.0	30°/45°	31-37.5	32.5-44	250/251	3 + 3	TW505	140 + 150 + 200
201	35.0	31°/46°	31.5-38	31.5-44	250/251	3 + 3	TW505	140 + 150 + 200
618	35.0	35°/60°	32-37.5	32-42	250/252	5 + 5	TW505	140 + 150 + 200
720	38.0	0°	35-45.7		251	3	TW505	140 + 150 + 200
213	38.0	15°/60°	34.5-45	34.5-49	251/254	3 + 3	TW505	140 + 150 + 200
217	38.0	15°/75°	34.5-45	34.5-45	251/254	3 + 3	TW505	140 + 150 + 200
297	38.0	15°/70°	35-45	35-45.5	251/254	3 + 3	TW505	140 + 150 + 200
234	38.0	30°/45°	35-45	35-47	251	3 + 3	TW505	140 + 150 + 200

Frees nr. serie 200 600 + 700	Body Ø mm	Hoeken	Freesbereik mm		Mesjes nr.	Aantal	T-sleutel	Geleiderpen/Pilot
626	38.0	30°/45°	35-45	35-47	251	5 + 5	TW505	140 + 150 + 200
208	38.0	31°/46°	35-45	35-47	251	3 + 3	TW505	140 + 150 + 200
622	38.0	31°/46°	35-45	35-47	251	5 + 5	TW505	140 + 150 + 200
275	38.0	46°	35-47		251	3	TW505	140 + 150 + 200
205	38.0	60°	35-47.5		254	3	TW505	140 + 150 + 200
271	38.0	70°	35-46.5		254	3	TW505	140 + 150 + 200
635	41.3	15°/45°	38-47.5	38-50	251	5 + 5	TW505	140 + 150 + 200
633	41.3	20°/45°	38-48.5	38-49.5	251	5 + 5	TW505	140 + 150 + 200
237	41.3	30°/45°	38-48.5	38-50	251	3 + 3	TW505	140 + 150 + 200
632	41.3	31°/46°	38-49	38-50	251	5 + 5	TW505	140 + 150 + 200
634	41.3	45°	38-50		251	5	TW505	140 + 150 + 200
740	44.5	0°	41.5-50.8		251	3	TW505	140 + 150 + 200
292	44.5	15°/60°	41-51	41-54.5	251/254	3 + 3	TW505	140 + 150 + 200
641	44.5	15°/46°	41-51	41-52.5	251	3 + 5	TW505	140 + 150 + 200
643	44.5	15°/60°	41-51	41-54.5	251/254	5 + 5	TW505	140 + 150 + 200
697	44.5	15°/75°	41-51	41-52	251/254	5 + 5	TW505	140 + 150 + 200
645	44.5	30°/45°	41-51.5	41-52.5	251	5 + 5	TW505	140 + 150 + 200
642	44.5	31°/46°	41-51.5	41-52.5	251	5 + 5	TW505	140 + 150 + 200
695	44.5	35°	41-52.5		251	5	TW505	140 + 150 + 200
698	44.5	37.5°	41-53.5		251	5	TW505	140 + 150 + 200
293	44.5	60°	41-54.5		254	3	TW505	140 + 150 + 200
272	44.5	75°	41-51.5		254	3	TW505	140 + 150 + 200
750	50.8	0°	47.8-57.2		251	3	TW505	140 + 150 + 200
288	50.8	15°/60°	47.5-56.5	47.5-61	251/254	3 + 3	TW505	140 + 150 + 200
654	50.8	15°/75°	47.5-56.5	47.5-58	251/254	5 + 5	TW505	140 + 150 + 200
660	50.8	30°/45°	47.5-58	47.5-59	251	5 + 5	TW505	140 + 150 + 200
680	50.8	30°	47.5-58.5		251	5	TW505	140 + 150 + 200
652	50.8	31°/46°	47.5-58	47.5-59	251	5 + 5	TW505	140 + 150 + 200

Frees nr. serie 200 600 + 700	Body Ø mm	Hoeken	Freesbereik mm	Mesjes nr.	Aantal	T-sleutel	Geleiderpen/Pilot
683	50.8	36°	47.5-58	251	5	TW505	140 + 150 + 200
657	50.8	60°	47.5-60.5	254	5	TW505	140 + 150 + 200
276	50.8	70°	47.5-58	254	3	TW505	140 + 150 + 200
664	57.2	15°/46°	54-64	251	5 + 9	TW505	140 + 150 + 200
665	57.2	30°/45°	54-63.5	251	7 + 7	TW505	140 + 150 + 200
674	63.5	15°/60°	60.5-70.5	251/254	5 + 5	TW505	140 + 150 + 200
672	63.5	31°/46°	60.5-70.5	251	7 + 7	TW505	140 + 150 + 200
675	63.5	60°	60.5-73	254	5	TW505	140 + 150 + 200

Cartech B.V. h/o Superspark

Boekweitskorrel 9a

NL-1251 ZH Laren

Tel. + 31 35 53 89 504

www.superspark.nl

info@superspark.nl